



Тип покрытия:	Резина	
Возможное назначение:	<p>Production of metal strip : pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments</p> <p>Diverse applications in a lot of industrial areas : textile, packaging, (card)board, plastic film, converting, glass, wood etc.</p> <p>Rollers and wheels in contact with oil, fuel or grease, even at higher temperature</p>	
Диапазон твердости:	65 Shore A	
Доступные цвета:	бежевый	
Рекомендуемая толщина покрытия:	мин. 10 mm - макс. 25 mm	
Температурная стойкость:	сухие условия:	постоянно 90°C / пиковые значения 110°C
	влажные условия:	постоянно 60°C / пиковые значения 80°C
Характеристики и преимущества:	<p>Excellent resistance to mineral and vegetal oil, fuel, grease and (animal) fat</p> <p>Very good physical properties, tear and abrasion resistance, good elasticity and resilience</p> <p>Non-staining in contact with delicate substrates</p> <p>Good and stable grip in contact with most substrates</p> <p>Very good squeegee and wipe-off behavior</p>	
Химическая стойкость:	Кислотные растворы: Щелочные растворы: Горячая вода и пар: Озон: Смазочные материалы: Ароматические растворители (толуол, бензол, ...): Хлорированные растворы: Полярные растворители(MEK, ацетон,...):	Хорошо Очень хорошо Хорошо Хорошо Отлично Умеренно Не подходит Не подходит
Рекомендуемые средства очистки:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpine, white spirit	

Optidraw
